

TECHNICAL INFORMATION

Physical properties

Total Weight: 300g/m² (nominal)
 Vinyl Weight: 210g/m² (nominal)
 Substrate Type: **Paper** (Uncoated mechanical wallpaper base comprising bleached and unbleached cellulose and unbleached mechanical wood pulp)
 Substrate Weight 90g/m² (nominal)

Roll size:

130cm x 30m (normally) - cut lengths available

Pattern Repeat

Free Match

Impact Resistance

Pass

Fire Rating:

Class 'O' to the requirements of Approved Document B of the British Building Regulations (Class 1, BS476 Part 7). Euroclass B - s1, d0.

Adhesive:

Newmor Light or Standard.
 Varies with substrate - please enquire.

Light Fast:

BSEN20105 (min) 6

Light reflective value (LRV)

Available on request.
 In architecture, light reflectance value, is a measure of visible and usable light that is reflected from a surface when illuminated by a light source.

Specifications

Conforms to requirements of BS EN 15102:2007 and BS EN 259

Stain/Chemical Resistance:

Pass ASTM D-1308-1987 Federal Spot Test. Resistant to temporary staining of oils, fats, mild acids and alkalis.

Quality Assurance:

Our management systems and production procedures comply with ISO 9001 : 2015, the internationally recognised Quality Standard.

Availability:

Special

Origin:

Designed, coloured, manufactured and stocked in the UK.

Warranty:

Newmor offers a five year warranty against manufacturing defects. Full details available on application.

Samples:

Larger samples are readily available on request.

Maintenance:

Fully washable and durable