

TECHNICAL INFORMATION

Physical properties

Total weight: 300gsm
Vinyl Weight: 210gsm
Substrate Type: Paper
Substrate weight: 90gsm

Type II and other specifications available

Tensile Strength: MD 40 N/cm (nominal)
TD 25 N/cm (nominal)
Tear Strength: 2200 mN (nominal)

Roll size:

1.3m x 50m - cut lengths available

Pattern Repeat:

Vertical: Free Match

Fire Rating:

Fire Rating:
Class 'O' to the requirements of Approved Document B of the British Building Regulations (Class 1, BS 476 part 7).
Euroclass B - s2, d0.

Adhesive:

Paper backed vinyls - Newmor Light.
Varies with substrate - please enquire.

Bacteria Resistance:

Contains an active Fungicide.

Light Fast:

BS EN ISO 20105 min 6

LRV

Available on Request

Specifications

Conforms to requirements of BS EN 15102, BS EN 259 and Federal Specification CCC-W-408A & C CFFA Quality Standard for Vinyl Coated Fabric Wallcoverings CFFA-W-101A

Stain/Chemical Resistance:

Pass ASTM D-1308-1987 Federal Spot Test.
Resistant to temporary staining of oils, fats, mild acids and alkalis.

Quality Assurance:

All management systems and production procedures comply with ISO 9001, the internationally recognised Quality Standard.

Availability:

Every product stocked in depth.
5.00pm deadline for next day delivery (UK only).

Origin:

Designed, coloured, manufactured and stocked in the UK.

Warranty:

Newmor offers a five year warranty against manufacturing defects.
Full details available on application.

Samples:

Larger samples are readily available on request.

Maintenance:

Fully washable and in most cases products can be scrubbed repeatedly to remove any marks without damaging the product itself.
Most products are also able to withstand



Global Support



Newmor
WALLCOVERINGS

UK SALES:

T: 01938 551990
E: sales@newmor.com

EXPORT SALES:

T: + 44 (0) 1938 55 2671
E: enquires@newmor.com