

# TECHNICAL INFORMATION

## Physical properties

Total weight: 400g/m<sup>2</sup>  
 Vinyl Weight: 310g/m<sup>2</sup>  
 Substrate Type: Non-Woven Fabric  
 Substrate weight: 90g/m<sup>2</sup>

## Type II and other specifications available

Tensile Strength: MD 40 N/cm (nominal)  
 TD 30 N/cm (nominal)  
 Tear Strength: 4500 mN (nominal)

## Roll size:

127cm x 30m - cut lengths available

## Pattern Repeat

Canopy: V: 530mm, H: 1220mm  
 Flute: V: 265mm, H: 152.5mm  
 Fold: V: 132.5mm, H: 152.5mm  
 Furl: V: 265mm, H: 61mm  
 Luna: V: 530mm, H: 610mm  
 Origami: V: 176mm, H: 176mm  
 Shade: V: 176mm, H: 203mm  
 Wave: V: 203.3m, H: 406mm

## Fire Rating:

Class 'O' to the requirements of Approved Document B of the British Building Regulations (Class 1, BS 476 part 7).  
 Euroclass B - s2, d0. Class A ASTM E-84 Tunnel Test.

## Adhesive:

Fabric backed vinyls - Newmor Heavy.  
 Varies with substrate - please enquire.

## Bacteria Resistance:

Manufactured to include antimicrobial protection as standard to help in the control of fungi, actinomycetes and bacteria.

## Light Fast:

Excellent Light Fastness  
 BS EN ISO 105-B02 min. 7/8

LRV = Light reflective value

## Specifications

Conforms to requirements of BS EN 15102, BS EN 259 and Federal Specification CCC-W-408A & C CFFA Quality Standard for Vinyl Coated Fabric Wallcoverings CFFA-W-101A

## Stain/Chemical Resistance:

Pass ASTM D-1308-1987 Federal Spot Test.  
 Resistant to temporary staining of oils, fats, mild acids and alkalis.

## Quality Assurance:

All management systems and production procedures comply with ISO 9001, the internationally recognised Quality Standard.

## Availability:

Every product stocked in depth.  
 5.00pm deadline for next day delivery.  
 (UK only)

## Origin:

Designed, coloured, manufactured and stocked in the UK.

## Warranty:

Newmor offers a five year warranty against manufacturing defects.  
 Full details available on application.

## Samples:

Larger samples are readily available on request.

## Maintenance:

Fully washable and in most cases products can be scrubbed repeatedly to remove any marks without damaging the product itself. Most products are also able to withstand the use of chlorine cleaning agents.



British Product | Global Support

Customise this design



youchoose™

Our Unique Re-Colouration Service

www.newmor.com

STUDIO COLLECTION



Newmor  
WALLCOVERINGS

UK SALES:

T: 0870 606 1237

E: sales@newmor.com

EXPORT SALES:

T: + 44 (0) 1938 55 2671

E: enquires@newmor.com