

TECHNICAL INFORMATION

**Physical properties**Total weight: 460g/m² (nominal)Vinyl Weight: 400g/m² (nominal)Substrate Type: Woven Polyester/Cotton
Scrim - "Protex"Substrate weight: 60g/m² (nominal)**Other specifications available**

Tensile Strength: MD 80 N/cm (nominal)

TD 60 N/cm (nominal)

Tear Strength: 8500 mN (nominal)

**Roll size:**

130cm x 30m - cut lengths available

**Pattern Repeat:**

Reverse hang, straight match

**Fire Rating:**

Class 'O' to the requirements of Approved

Document B of the British Building

Regulations. Euroclass B - s1, d0.

Class A ASTM E-84 Tunnel Test.

**Adhesive:**Fabric backed vinyls - Newmor Heavy. Varies
with substrate - please enquire.**Bacteria Resistance:**

Contains an active Fungicide.

**Light Fast:**

Excellent Light Fastness

BS EN ISO 105-B02 7/8

LRV = Light reflective value

Available on request

Specifications:Conforms to requirements of BS EN 15102, BS
EN 259 and WA Quality Standard W-101.**Stain/Chemical Resistance:**

Pass ASTM D-1308-1987 Federal Spot Test.

Resistant to temporary staining of oils,
fats, mild acids and alkalis.**Quality Assurance:**Our management system and production
procedures comply with ISO9001: 2015, the
internationally recognised Quality Standard.**Availability:**

Every product stocked in depth.

5.00pm deadline for next day delivery.

(UK only)

Origin:Designed, coloured, manufactured and stocked
in the UK.**Warranty:**Newmor offers a five year warranty
against manufacturing defects.

Full details available on application.

Samples:

Larger samples are readily available on request.

Maintenance:Fully washable and in most cases products can
be scrubbed repeatedly to remove any marks
without damaging the product itself. Also able
to withstand the use of chlorine releasing
agent solutions.MADE IN GREAT BRITAIN
British Product | Global Support