

## TECHNICAL INFORMATION

### Physical properties

Total Weight: 460gsm (nominal)  
 Vinyl Weight: 355gsm (nominal)  
 Substrate Type: Nonwoven Fabric  
 Substrate Weight: 105gsm (nominal)

Tensile Strength: MD 80 N/cm (nominal)  
 TD 60 N/cm (nominal)  
 Tear Strength: 8500 mN (nominal)

### Roll size:

130cm x 30m - cut lengths available

### Fire Rating:

Class B when bonded to a suitable  
 substrate ASTM E-84 Class A

### Adhesive:

Fabric backed vinyls - Newmor Heavy.  
 Varies with substrate - please enquire.

### Bacteria Resistance:

Contains an active Fungicide.

### Light Fast:

Excellent Light Fastness  
 BS EN ISO 105-B02 7/8

### Light reflective value (LRV)

In architecture, light reflectance value, is a  
 measure of visible and usable light that is  
 reflected from a surface when illuminated  
 by a light source.

### Specifications

Conforms to requirements of BS EN 15102,  
 BS EN 259 and WA – Quality Standard W-101.

### Stain/Chemical Resistance:

Resistant to temporary staining of oils,  
 fats, mild acids and alkalis.

### Quality Assurance:

Our management systems and production  
 procedures comply with ISO 9001 : 2015,  
 the internationally recognised Quality  
 Standard.

### Origin:

Designed, coloured, manufactured and  
 stocked in the UK.

### Warranty:

Newmor offers a five year warranty  
 against manufacturing defects.

### Samples:

Larger samples are readily available on  
 request.

### Maintenance:

Fully washable and in most cases products  
 can be scrubbed repeatedly to remove any  
 marks without damaging the product itself.  
 Also able to withstand the use of chlorine  
 releasing agent solutions.

