TECHNICAL INFORMATION

Physical properties
Total Weight: 460g/m² (nominal)
Vinyl Weight: 355g/m² (nominal)
Substrate Type: Nonwoven Fabric
Substrate Weight: 105g/m² (nominal)

Type II and other specifications available
Tensile Strength: MD 80 N/cm (nominal)
TD 60 N/cm (nominal)
Tear Strength: 8500 mN (nominal)

Roll size:
130cm x 30m (normally) - cut lengths available

Pattern Repeat
Reverse Hang, Free Match

Fire Rating:
Class B when bonded to a suitable substrate
ASTME-84 Class A

Adhesive:
Newmor Heavy.
Varies with substrate - please enquire.

Bacteria Resistance:
Contains an active Fungicide.

Light Fast:
Excellent Light Fastness
BS EN ISO 105-B02 7/8

Light reflective value (LRV)
Available on request.
In architecture, light reflectance value, is a measure of visible and usable light that is reflected from a surface when illuminated by a light source.

Specifications
Conforms to requirements of BS EN 15102 EN 259 and WA – Quality Standard W-101.

Stain/Chemical Resistance:
Pass ASTM D-1308-1987 Federal Spot Test.
Resistant to temporary staining of oils, fats, mild acids and alkalis.

Quality Assurance:
Our management systems and production procedures comply with ISO 9001 : 2015, the internationally recognised Quality Standard.

Availability:
Every product stocked in depth.
5.00pm deadline for next day delivery.
(UK only)

Origin:
Designed, coloured, manufactured and stocked in the UK.

Warranty:
Newmor offers a five year warranty against manufacturing defects.
Full details available on application.

Samples:
Larger samples are readily available on request.

Maintenance:
Fully washable and in most cases products can be scrubbed repeatedly to remove any marks without damaging the product itself. Also able to withstand the use of chlorine releasing agent solutions.

20% This product contains at least 20% recycled material